NASA / TM-1999-209552

Flight Data Reduction of Wake Velocity Measurements Using an Instrumented OV-10 Airplane

Dan D. Vicroy, Robert A. Stuever, Eric C. Stewart, and Robert A. Rivers
Langley Research Center, Hampton, Virginia

September 1999

The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- TECHNICAL PUBLICATION. Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.

- TECHNICAL MEMORANDUM. Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.

- CONTRACTOR REPORT. Scientific and technical findings by NASA-sponsored contractors and grantees.

- CONFERENCE PUBLICATION. Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.

- SPECIAL PUBLICATION. Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.

- TECHNICAL TRANSLATION. English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results ... even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at ***http://www.sti.nasa.gov***

- E-mail your question via the Internet to help@sti.nasa.gov

- Fax your question to the NASA STI Help Desk at (301) 621-0134

- Phone the NASA STI Help Desk at (301) 621-0390

- Write to:
  NASA STI Help Desk
  NASA Center for AeroSpace Information
  7121 Standard Drive
  Hanover, MD 21076-1320

NASA / TM-1999-209552



Flight Data Reduction of Wake Velocity Measurements Using an Instrumented OV-10 Airplane

Dan D. Vicroy, Robert A. Stuever, Eric C. Stewart, and Robert A. Rivers
Langley Research Center, Hampton, Virginia

National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23681-2199

September 1999

Available from:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 605-6000

Contents

Abstract

A series of flight tests to measure the wake of a Lockheed C-130 airplane and the accompanying atmospheric state have been conducted. A specially instrumented North American Rockwell OV-10 airplane was used to measure the wake and atmospheric conditions. An integrated database has been compiled for wake characterization and validation of wake vortex computational models. This paper describes the wake-measurement flight-data reduction process.

Introduction

Several of today's major airports are operating their capacity limit, leading to an increase in airport congestion and delays. As more and more airplanes are placed into the terminal area the probability of encountering wake turbulence is increased. A wake vortex upset is most hazardous for aircraft near the ground during landing and takeoff. The degree of upset mainly depends on the relative sizes of the vortex generating and vortex encountering airplanes, and the extent of wake decay. The rate of wake decay is highly dependent on the atmospheric state.

Numerous laboratory experiments and analytical models have been developed to study and simulate wake vortex flow physics. However, there is very little full-scale data available for comparison with and validation of the experimental and computational results. Many of the previous wake-measurement flight tests have omitted the atmospheric state data, which has a direct influence on wake flow physics. The National Aeronautics and Space Administration (NASA) conducted a series of flight tests to develop a wake-measurement data set with the accompanying atmospheric state information. This data set has been compiled into a database that can be used by wake vortex researchers to compare with experimental and computational results. Details of the database are provided in reference 1. This report describes the wake-measurement flight-data reduction process.

Symbols

a	speed of sound, fps
b_{C130}	wing span of C-130, ft
b_{α}	angle of attack position error calibration bias, deg
b_{β}	sideslip position error calibration bias, deg
$b_{\Delta Pq}$	position error pressure correction bias, psi
$b_{\Delta Pq\beta_n}$	nose-boom position error pressure correction due to sideslip bias, psi
$b_{\Delta Pq\beta 1}, b_{\Delta Pq\beta 2}$	wing-boom position error pressure correction due to sideslip bias terms, psi
b_{η}	flank angle position error calibration bias, deg
C_a	5-hole probe angle of attack calibration curve coefficient

C_b	5-hole probe sideslip calibration curve coefficient
Cor_E	east velocity integration correction factor
Cor_N	north velocity integration correction factor
Cor_Z	vertical velocity integration correction factor
C_q	dynamic pressure calibration coefficient
C_s	static pressure calibration coefficient
C_α	5-hole probe angle of attack coefficient
C_β	5-hole probe sideslip coefficient
d_E	distance east of wake origin, ft
$d_{E_{GPS}}$	east distance computed from GPS, ft
$d_{E_{INS}}$	east distance computed from integrated inertial velocity, ft
d_{E_o}	wake origin east offset distance, ft
d_N	distance north of wake origin, ft
$d_{N_{GPS}}$	north distance computed from GPS, ft
$d_{N_{INS}}$	north distance computed from integrated inertial velocity, ft
d_{N_o}	wake origin north offset distance, ft
d_{wk}	wake drift distance, ft
d_Z	vertical distance below wake origin, ft
$d_{Z_{GPS}}$	vertical distance computed from GPS, ft
$d_{Z_{INS}}$	vertical distance computed from integrated inertial velocity, ft
d_{Z_o}	wake origin vertical offset distance, ft
$drift_x$	longitudinal wake drift distance in wake axis system, ft
$drift_y$	lateral wake drift distance in wake axis system, ft
$\dot{E}$	airplane inertial velocity component east, fps
g	gravitational acceleration, 32.2 ft/s^2

h	altitude, ft
h_{grnd}	altitude at the ground, ft
h_{pass}	altitude of a pass, ft
HI	GPS geometric altitude, meters
i	array index variable
j	array index variable
k_{α}	linear slope of angle of attack position error calibration
k_{β}	linear slope of sideslip position error calibration
$k_{\Delta Pq}$	linear slope of position error pressure correction
$k_{\Delta Pq_{\beta_n}}$	linear slope of nose-boom position error pressure correction due to sideslip
$k_{\Delta Pq_{\beta 1}}, k_{\Delta Pq_{\beta 2}}$	linear slope of wing-boom position error pressure correction due to sideslip
k_{η}	linear slope of flank angle position error calibration
K	temperature recovery factor (0.995)
Lat	latitude, deg
Lat_a	latitude of point *a*, deg
Lat_b	latitude of point *b*, deg
$Lat_{C_{ref}}$	latitude of C-130 at t_{ref} , deg
Lat_N	latitude north, deg
Lat_o	latitude of wake origin location, deg
$Lat_{OV_{ref}}$	latitude of OV-10 at t_{ref} , deg
$Lat_{OV_{start}}$	latitude of OV-10 at t_{start}, deg
$Lat_{OV_{stop}}$	latitude of OV-10 at t_{stop} , deg
Lng	longitude, deg
Lng_a	longitude of point *a*, deg
Lng_b	longitude of point *b*, deg

$Lng_{C_{ref}}$	longitude of C-130 at t_{ref} , deg
Lng_o	longitude of wake origin location, deg
$Lng_{OV_{ref}}$	longitude of OV-10 at t_{ref} , deg
$Lng_{OV_{start}}$	longitude of OV-10 at t_{start}, deg
$Lng_{OV_{stop}}$	longitude of OV-10 at t_{stop} , deg
Lng_W	longitude west, deg
M	Mach number
Mag_{var}	magnetic variation
$\dot{N}$	airplane inertial velocity component north, fps
Outfile	Wake_Vel output file name
p_m	roll rate from mechanical gyro, deg/sec
PDOP	dilution of precision parameter
P_o	standard sea-level static pressure, 2116.22 psf
P_{ref}	reference pressure, 1000 millibars
Ps	static pressure, psi
Ps_c	probe calibration corrected static pressure, psi
Ps_o	static pressure corrected for zero bias, psi
P_3	5-hole probe center port pressure, psi
$P_{\alpha 1}$	5-hole probe bottom port pressure, psi
$P_{\alpha 2}$	5-hole probe top port pressure, psi
$P_{\beta 1}$	5-hole probe right port pressure, psi
$P_{\beta 2}$	5-hole probe left port pressure, psi
q	dynamic pressure, psi
q_c	probe calibration corrected dynamic pressure, psi
q_m	pitch rate from mechanical gyro, deg/sec

q_o	dynamic pressure corrected for zero bias, psi
r_m	yaw rate from mechanical gyro, deg/sec
R	gas constant, 1716.5 ft lb/(slug °R)
RMS	root mean squared position error, meters
Rng	range from one point to another, n. mi.
Rng_{err}	range error, n. mi.
Rng_{min}	minimum range error value, n. mi.
SV	number of navigation satellites received
t	time, sec
t_{GPS}	global positioning system time, sec
t_o	time when encountered wake was generated, sec
t_{pass}	time of pass, sec
t_{start}	event start time, sec
t_{stop}	event stop time, sec
t_{ref}	time of vortex encounter, sec
T_{abs}	absolute total air temperature, °R
$\mathbf{T}_{be}$	body axis to Earth axis transformation matrix
$\mathbf{T}_{ew}$	Earth axis to wake axis transformation matrix
T_m	total air temperature, °C
T_o	standard sea-level temperature, 518.67 °R
T_θ	potential temperature, °R
T_∞	free-stream air temperature, °R
u_b	body-axis longitudinal airspeed component, fps
u_e	Earth-axis longitudinal airspeed component, fps
v_b	body-axis lateral airspeed component, fps

v_e	Earth-axis lateral airspeed component, fps
$Vrtx$	vortex identifier (L for left, R for right)
Vt	true airspeed, fps
Vt_{loc}	local true airspeed, fps
V_{wnd}	wind speed, knots
w_b	body-axis vertical airspeed component, fps
w_e	Earth-axis vertical airspeed component, fps
W_E	Earth-axis easterly wind component, fps
W_N	Earth-axis northerly wind component, fps
Wnd_{Dir}	wind direction, degrees magnetic
Wnd_E	easterly wind component, fps
Wnd_N	northerly wind component, fps
Wnd_{Spd}	wind speed, knots
Wnd_x	longitudinal wind component in the wake axis system, fps
Wnd_y	lateral wind component in the wake axis system, fps
W_Z	Earth-axis vertical wind component, fps
x, y, z	airplane axis coordinates, ft
x_b, y_b, z_b	airplane axis coordinates of the body-axis origin, ft
$x_{o_w}, y_{o_w}, z_{o_w}$	wake axis coordinates of the body-axis origin, ft
Z	geometric altitude, ft
Z_o	geometric altitude of wake origin location, ft
$Z_{OV_{start}}$	geometric altitude of OV-10 at t_{start}, ft
$Z_{OV_{stop}}$	geometric altitude of OV-10 at t_{stop}, ft
$\dot{Z}$	airplane inertial velocity component up, fps
α	angle of attack, deg

α_t	angle of attack corrected for airplane rotation rates, deg
α_{Vn}	wing tip alpha vane measurement, deg
β	sideslip angle, deg
β_t	sideslip angle corrected for airplane rotation rates, deg
β_{Vn}	wing tip beta vane measurement, deg
γ	specific heat ratio for air, 1.40
η	flank angle, deg
ξ	dummy variable
ρ	air density, slug/ft^3
ρ_{grnd}	air density at the ground, slug/ft^3
ρ_{mid}	air density at middle altitude, slug/ft^3
ρ_o	standard sea-level air density, 0.0023769 slug/ft^3
θ	pitch angle, deg
ϕ	roll angle, deg
ψ	yaw angle, deg
Ψ	heading, deg
Ψ_w	heading of wake axis system, deg
Ψ_{wnd}	wind direction, deg
ΔPq	position-error pressure correction, psi
ΔPq_β	position-error pressure correction due to sideslip, psi
$\Delta P_{\alpha 12}$	pressure difference between 5-hole probe bottom and top ports, psi
$\Delta P_{\beta 12}$	pressure difference between 5-hole probe right and left ports, psi
$\Delta P_{3\alpha 1}$	pressure difference between 5-hole probe center and bottom ports, psi
$\Delta P_{3\beta 1}$	pressure difference between 5-hole probe center and right ports, psi
Δt	wake age, sec

Subscripts

abs	absolute value
avg	average value
Bias	zero bias correction
C130	C-130 value
e	Earth axis system
Fit	from least-squares linear fit
grnd	value at the ground
l	left boom
mag	degrees magnetic
n	nose boom
pass	value during a pass
probe	probe measured value
r	right boom
ref	reference value
tip	C-130 wing tip value
w	wake axis system
wk	wake value
wnd	wind
5	5-hole probe
93	Litton LN-93 INU value

Superscripts

`	raw, uncorrected measurement

Abbreviations

a/c	aircraft

CPT	control position transducer
DAS	experimental data acquisition system
INU	inertial navigation unit
GPS	global positioning system
LAFB	Langley Airforce Base
NACA	National Advisory Committee for Aeronautics
NASA	National Aeronautics and Space Administration
PCM	pulse code modulation
OVDRA	OV-10 data reduction and analysis program
SCADC	standard central air-data computer
UTC	Coordinated Universal Time
Wake_Vel	wake velocity program

Flight Test Overview

The objective of the wake-measurement flight tests was to develop a full-scale data set with the accompanying atmospheric state information. The tests used two NASA airplanes as illustrated in figure 1.

The NASA Wallops Flight Facility's Lockheed C-130, shown in figure 2, was the wake generator. It was outfitted with wing tip smokers to mark the wake. It weighed between 105,000 and 95,000 pounds during the test and has a wingspan of 132 feet 7 inches. The tests were all flown with the C-130 in the clean (flaps up, gear up) configuration.

The NASA Langley's North American Rockwell OV-10A measured the wake and atmospheric conditions. The OV-10 was equipped with a three-boom, flow-sensor arrangement to measure the flow field characteristics of the wake. The booms were located on each wing tip and the right side of the nose as shown in figure 3. The OV-10 instrumentation is described in more detail in the next section. The OV-10 flew through the wake at various downstream distances measuring the wake velocities and position. A picture of a wake taken from the video camera mounted on the left tail is shown in figure 4. The smoke clearly denotes the two vortices.

The general flight test procedure was as follows. The OV-10 would fly to the flight test area and begin a series of "weather" runs. These would begin with one or two "turbulence" runs, which were 2-minute, level, constant heading flight segments 1000 feet below the test altitude. The test altitude was generally 4000 or 5000 feet. This was followed by a "weather profile" run, which was a constant speed, constant heading climb from 1000 feet below to 500 feet above the test altitude. Another series turbulence runs would then follow 500 feet above the test altitude. After completing the weather runs the

OV-10 would rendezvous with the C-130 and begin a series of "wake measurement" runs. The C-130 would fly a constant speed and heading at the test altitude. The OV-10 measured the wake by flying slower than the C-130 and making a series of wake penetrations at increasing ranges behind the C-130. At the conclusion of a series of wake measurement runs an additional series of weather runs were then conducted.

OV-10 Instrumentation

Significant modifications to the OV-10 were required to convert it from a stock aircraft into a research platform. An overview of the development of the research systems and measurement capabilities of the OV-10 is presented in reference 2. The following section provides a summary of the research instrumentation and experimental data system.

General System

A data acquisition system (DAS) was developed to collect and convert the analog signals from the experimental sensors and convert them into digital form for display, transmission, and recording. The system could record approximately two hours of data from 150 parameters at data rates up to 128 Hz. The major experimental instrumentation components are labeled in figure 3. The sensor outputs were signal conditioned, multiplexed and digitized by a commercial 12-bit pulse code modulation (PCM) subsystem that features functional flexibility, programmability, and the ability to multiplex analog and digital signals into a serial format. Major components of the sensor suite include:

- time-code generator to provide an accurate time base for all flight measurements,
- ring-laser-gyro inertial navigation unit (INU),
- global positioning system (GPS),
- standard central air-data computer (SCADC),
- fast-response rate and attitude gyros,
- two pitot-static and flow-angle-measurement systems,
- 5-hole airspeed and flow-angle probe,
- temperature probes,
- dew-point sensor,
- video/audio cameras/recorders,
- control position transducers (CPTs).

Except for sensors, displays, and control panels, most of the equipment for the DAS system is installed in the OV-10 cargo bay. A removable main instrumentation pallet, designed to fit in the aft portion of the cargo bay and roll out onto a cart for system maintenance, was fabricated and populated with equipment (Figures 5a and b). The forward part of the cargo bay housed the majority of the navigation, avionics and display equipment (Figure 6).

Navigation Systems

Three satellite based navigation systems have been added to the OV-10. The first is a multi-

component system that supports the research measurements and includes a Litton LN-93 ring-laser gyro INU integrated with a Honeywell 3A GPS receiver and a CPU-140/A SCADC. All the components communicate with the PCM system via a MIL-standard 1553 data bus through an 80486-processor/33-MHz personal-computer bus controller. The INU updates the GPS in the event of satellite signal loss, but the GPS does not update the INU position estimate. The INU also is capable of providing aircraft accelerations, velocities, and attitudes. Supplemental measurements of the linear accelerations and angular rates are provided by a separate package of fast-response rate gyros and accelerometers. The components of the research navigation system reside in the forward cargo bay on fixed plates and are not part of the removable instrument pallet. The second GPS system is an Ashtech Z12 system capable of storing 4 hours of position and velocity data at 1 Hz data rate. The third navigation system entails a Garmin GPS 100 mounted in the forward cockpit, and enables the pilot to precisely navigate and/or set up research maneuvers.

Air-Data Systems

There are two air-data systems on the OV-10. One system is the SCADC previously described, which is coupled to the INU/GPS system. The second system is the three-component pitot, static, and flow-direction measurement system described here.

Sensors mounted on the tips of graphite-epoxy research booms facilitate air data measurements at both wingtips and the nose. As is customary, the booms were designed to place sensors as far ahead of the predicted aircraft upwash influence as possible, yet have enough lightness and stiffness (high natural frequency) to prevent unwanted vibration influence on the sensor measurements. Thermally-controlled Setra pressure transducers, located approximately at the base of each respective research boom, provide for enhanced accuracy in pressure measurements. Accelerometers mounted near the tips of these booms provide information on boom vibration.

A standard National Advisory Committee for Aeronautics (NACA) pitot-static probe with balsa angle of attack and sideslip vanes, shown in figure 7, was mounted at the end of each wingtip boom approximately one chord length in front of the wing leading edge. The static and total pressure ports were connected to the pressure transducers by 13 feet of 1/4-inch inside-diameter flexible tubing. The balsa vanes, which have a high natural frequency of about 0.18 Hz per knot of indicated airspeed in incompressible flow (reference 3), have a natural frequency of approximately 22 Hz at the nominal OV-10 airspeed of 120 knots.

A Rosemount Model 858 AJ 5-hole probe, shown in figure 8, was mounted at the end of the nose boom. The Rosemount probe provides the required pressure ports for determining flow direction, airspeed, and altimetry measurements at the nose. The five pressure ports at the tip of the probe and the ring of static pressure ports about 3.5 inches aft are connected to a manifold such that the following pressure differences between the ports shown in figure 8 are measured.

$$\Delta P_{\alpha 12}{}' = P_{\alpha 1} - P_{\alpha 2} \quad \text{(psi)} \tag{1}$$

$$\Delta P_{\beta 12}{}' = P_{\beta 1} - P_{\beta 2} \quad \text{(psi)} \tag{2}$$

$$\Delta P_{3\alpha 1}{}' = P_{3} - P_{\alpha 1} \quad \text{(psi)} \tag{3}$$

$$\Delta P_{3\beta 1}{}' = P_3 - P_{\beta 1} \quad \text{(psi)} \tag{4}$$

$$q_n{}' = P_3 - Ps_n \quad \text{(psi)} \tag{5}$$

The tip of the mounted probe is approximately 6 feet in front of the aircraft nose and approximately 2 feet to the right of the longitudinal centerline. The probe was connected to the pressure transducers by approximately 17 feet of 3/16-inch inside-diameter flexible tubing. A small 0.067-inch inside diameter restrictor was inserted in each 3/16 tubing near the 5-hole probe. The restrictor size was experimentally selected per reference 4 to provide maximum damping to the pressure oscillations measured by the transducers when a 20 Hz sinusoidal pressure was applied to the probe.

A pair of Rosemount Model 102 non-deiced total temperature probes (one for the SCADC and one for the research system) and a General Eastern 1011 Aircraft Dew-Point Sensor are also integrated into the air-data system. The temperature probes are located on the underside of the wing approximately midway between each engine and wingtip. The dew-point sensor is mounted on the left side of the forward fuselage.

Airborne Video/Audio Systems

The research instrumentation includes a video/audio system consisting of three miniature lipstick-size Elmo video cameras and three recorders. One camera is located at the tip of the left vertical tail, pointing in the general direction of flight, and includes the top of the wing and fuselage in its field of view, as shown in figure 4. This camera provides a good, qualitative means of reviewing the highlights of a flight in preparation for data reduction and analysis. The other two cameras are mounted near the tip of each wing and are pointed vertically downward. The wing tip cameras provide a stereo recording capability that is post-processed to compute the spacing between the vortex smoke trails and distance from the OV-10. Audio channels on the video/audio system enable the pilot and flight test engineer to record verbal data during maneuvers.

Flight Data Reduction Process

The basic data flow of the flight data reduction process is shown in figure 9. From each flight four data products are generated directly from the OV-10.

- Time-tagged, video recordings from the tail camera and both wing-tip cameras.
- Flight notes from the test pilot and flight engineers of event times and conditions
- Time-tagged data tape from the experimental data system
- Ashtech differential GPS data

The flight notes and video data are reviewed and used to establish a precise log of event times and test conditions called the “flight event” file. This information is then used to extract from the experimental data tape the pre and post-flight instrument calibration data and data from special calibration flight maneuvers. This calibration data is used to establish the instrumentation zero bias values, which are saved as a “flight constants” file for each flight. The event and constants files and the data from the DAS are input for the **OV**-10 **D**ata **R**eduction and **A**nalysis Program (OVDRA). This program applies the instrument calibration and bias corrections to the DAS data and computes the inertial referenced wind components. Details of the OVDRA algorithms are presented in the *Calibration and Bias Corrections*

section of this report. The output of OVDRA is a calibrated data file for each run of the test flight. These run data files are used to characterize the atmosphere through wind and temperature profiles and turbulence calculations.

The wake velocity measurements are computed from the OVDRA output, the flight event file and the GPS position data from the OV-10 and the C-130. This information is input to the Wake Velocity Program (Wake_Vel) which computes the origin and age of the wake and translates the wind measurements to the wake axis system. Details of the Wake_Vel algorithms and the wake axis system are provided in the *Wake Velocity Calculation* section. The output of the Wake_Vel program is a data file for each wake measurement event of each run of each flight.

The pilot notes from the C-130 are used to estimate the initial circulation strength of the wake, which is required for subsequent wake decay analysis.

Calibration and Bias Corrections

The instrument calibrations and bias corrections are applied to the DAS data through the OVDRA program. All the recorded DAS data parameters are listed in table 1 along with their symbol and database name. All the data are interpolated to the highest sampling rate of 128 Hz. The sampling rates of all parameters are listed in the table. Those data parameters that do not have a symbol representation in table 1 are not used in the data reduction algorithms.

One of the primary functions of the OVDRA program is to translate the OV-10 atmospheric measurements from the airplane or body axis reference system, shown in figure 10 to an inertial reference system. This transformation is made through the yaw *(ψ)*, pitch *(θ)*, and roll *(ϕ)* Euler angles shown in figure 11.

The OVDRA program reads the DAS data at each time step and applies the following calculations.

Zero bias corrections

First the zero bias corrections are applied to the following parameters. The bias values were determined from pre-flight measurements with the airplane stationary in the hanger. These corrections compensate for shifts produced by the DAS signal conditioning circuitry.

- The static and dynamic pressure measurements from the left, nose and right booms, respectively.

$$Ps_{o_j} = Ps_j' - Ps_{j_{\text{Bias}}} \quad \text{(psi)} \qquad j = l,n,r \tag{6}$$

$$q_{o_j} = q_j' - q_{j_{\text{Bias}}} \quad \text{(psi)} \qquad j = l,n,r \tag{7}$$

- The pressure difference measurements across the nose boom 5-hole probe.

$$\Delta P_{\alpha 12} = \Delta P_{\alpha 12}' - \Delta P_{\alpha 12_{\text{Bias}}} \quad \text{(psi)} \tag{8}$$

$$\Delta P_{\beta 12} = \Delta P_{\beta 12}' - \Delta P_{\beta 12_{\text{Bias}}} \quad \text{(psi)} \tag{9}$$

$$\Delta P_{3\alpha 1} = \Delta P_{3\alpha 1}' - \Delta P_{3\alpha 1_{\text{Bias}}} \quad \text{(psi)} \tag{10}$$

$$\Delta P_{3\beta 1} = \Delta P_{3\beta 1}' - \Delta P_{3\beta 1_{\text{Bias}}} \quad \text{(psi)} \tag{11}$$

- The mechanical gyro measurements of roll, pitch and yaw rates, respectively.

$$p_m = p_m' - p_{m_{\text{Bias}}} \quad \text{(deg/sec)} \tag{12}$$

$$q_m = q_m' - q_{m_{\text{Bias}}} \quad \text{(deg/sec)} \tag{13}$$

$$r_m = r_m' - r_{m_{\text{Bias}}} \quad \text{(deg/sec)} \tag{14}$$

- The total temperature measurement.

$$T_m = T_m' - T_{m_{\text{Bias}}} \quad (^\circ\text{C}) \tag{15}$$

Rosemont 5-Hole Probe Calibration Correction

The first step in the 5-hole probe calibration correction is to compute the angle-of-attack and sideslip coefficients

$$C_\alpha = \frac{\Delta P_{\alpha 12}}{\frac{1}{2}\left(\Delta P_{3\beta 1} + \Delta P_{3\alpha 1}\right) + \frac{1}{4}\left(\Delta P_{\beta 12} + \Delta P_{\alpha 12}\right)} \tag{16}$$

$$C_\beta = \frac{\Delta P_{\beta 12}}{\frac{1}{2}\left(\Delta P_{3\beta 1} + \Delta P_{3\alpha 1}\right) + \frac{1}{4}\left(\Delta P_{\beta 12} + \Delta P_{\alpha 12}\right)} \tag{17}$$

A fifth-order two-dimensional polynomial calibration curve that is a function of C_α and C_β is then used to compute the local angle of attack and sideslip.

$$\alpha_5 = \sum_{i=0}^{4}\sum_{j=0}^{4} C_\alpha^j \cdot C_\beta^i \cdot C_{a_{5i+j+1}} \quad \text{(deg)} \tag{18}$$

$$\beta_5 = \sum_{i=0}^{4}\sum_{j=0}^{4} C_\alpha^j \cdot C_\beta^i \cdot C_{b_{5i+j+1}} \quad \text{(deg)} \tag{19}$$

The local dynamic and static pressure are computed in a similar manner.

$$q_5 = \frac{q_{o_n}}{1 - \sum_{i=0}^{4}\sum_{j=0}^{4} C_\alpha^j \cdot C_\beta^i \cdot C_{q_{5i+j+1}}} \quad \text{(psi)} \tag{20}$$

$$Ps_5 = Ps_{o_n} + q_5 \sum_{i=0}^{4}\sum_{j=0}^{4} C_\alpha^j \cdot C_\beta^i \cdot C_{s_{5i+j+1}} \quad \text{(psi)} \tag{21}$$

The values for the polynomial coefficients C_a, C_b, C_q and C_s were derived from proprietary manufacturer's data and independent wind tunnel tests.

Position Error Corrections to Local Flow Angle Measurements

The position error correction terms were derived from the airspeed calibration tests that are discussed in appendix A. The corrections to the local angle of attack measurements are:

$$\alpha_r = k_{\alpha_r} \cdot \alpha_{Vn_r} + b_{\alpha_r} \quad \text{(deg)} \tag{22}$$

$$\alpha_l = k_{\alpha_l} \cdot \alpha_{Vn_l} + b_{\alpha_l} \quad \text{(deg)} \tag{23}$$

$$\alpha_n = k_{\alpha_n} \cdot \alpha_5 + b_{\alpha_n} \quad \text{(deg)} \tag{24}$$

The vertical balsa vanes on the wing tip booms that are referred to as the sideslip or β vanes actually measure the flank angle rather than the true sideslip. The position corrections to the flank angle measurements are:

$$\eta_r = k_{\eta_r} \cdot \beta_{Vn_r} + b_{\eta_r} \quad \text{(deg)} \tag{25}$$

$$\eta_l = k_{\eta_l} \cdot \beta_{Vn_l} + b_{\eta_l} \quad \text{(deg)} \tag{26}$$

The sideslip angles are computed from the flank angle measurements through the trigonometric relationship.

$$\beta_j = \tan^{-1}\left(\tan\eta_j \cos\alpha_j\right) \quad \text{(deg)} \qquad j = r, l \tag{27}$$

The position correction for the nose boom sideslip measurement is:

$$\beta_n = k_{\beta_n} \cdot \beta_5 + b_{\beta_n} \quad \text{(deg)} \tag{28}$$

The baseline values for the position error correction terms (i.e. the *k* and *b* terms) are provided in table 2, which lists all the calibration constants. The *b* terms are modified for each flight based on data from pre and post-flight calibrations and in-flight calibration maneuvers.

NACA Pitot Probe Calibration Corrections

The NACA pitot probe measurements from each wing tip boom are corrected for local flow angle effects based on wind tunnel calibration data. The static and dynamic pressure correction coefficients, C_s and C_q respectively, are obtained from a 2-D table lookup as a function of the local angle of attack and sideslip. Tables 3 and 4 list the C_s and C_q coefficient values, respectively, as a function of the local angle of attack and sideslip. The dynamic and static pressure corrections are:

$$q_{c_j} = \frac{q_{o_j}}{1 - C_{q_j}} \qquad j = r, l \tag{29}$$

$$Ps_{c\,j} = Ps_{o_j} + C_{s_j} \cdot q_{c\,j} \qquad j = r, l \tag{30}$$

Position Error Corrections to Static and Dynamic Pressure Measurements

The position-error pressure correction terms were determined from the airspeed calibration tests and are developed in Appendix A. The correction terms were found to be a function of the local dynamic pressure and sideslip. The pressure correction terms are computed as:

$$\Delta Pq_j = k_{\Delta Pq_j} \cdot q_{c_j} + b_{\Delta Pq_j} + \Delta Pq_{\beta_j} \quad \text{(psi)} \qquad j = r, l \tag{31}$$

$$\Delta Pq_n = k_{\Delta Pq_n} \cdot q_5 + b_{\Delta Pq_n} + \Delta Pq_{\beta_n} \quad \text{(psi)} \tag{32}$$

where the sideslip correction is:

$$\Delta Pq_{\beta_n} = \text{Min}\left(0, k_{\Delta Pq_{\beta_n}} \cdot \left|\beta_n\right| + b_{\Delta Pq_{\beta_n}}\right) \quad \text{(psi)} \tag{33}$$

$$\Delta Pq_{\beta_r} = \begin{cases} k_{\Delta Pq_{\beta 1}} \cdot \beta_r + b_{\Delta Pq_{\beta 1}} & , \beta_r < 0 \\ k_{\Delta Pq_{\beta 2}} \cdot \beta_r + b_{\Delta Pq_{\beta 2}} & , \beta_r \geq 0 \end{cases} \quad \text{(psi)} \tag{34}$$

$$\Delta Pq_{\beta_l} = \begin{cases} -k_{\Delta Pq_{\beta 2}} \cdot \beta_l + b_{\Delta Pq_{\beta 2}} & , \beta_l < 0 \\ -k_{\Delta Pq_{\beta 1}} \cdot \beta_l + b_{\Delta Pq_{\beta 1}} & , \beta_l \geq 0 \end{cases} \quad \text{(psi)} \tag{35}$$

The position error pressure correction is applied to the static and dynamic pressure through:

$$Ps_j = Ps_{c\,j} - \Delta Pq_j \quad \text{(psi)} \qquad j = r, l \tag{36}$$

$$Ps_n = Ps_5 - \Delta Pq_n \quad \text{(psi)} \tag{37}$$

$$q_j = q_{c_j} + \Delta P q_j \quad \text{(psi)} \qquad j = r, l \tag{38}$$

$$q_n = q_5 + \Delta P q_n \quad \text{(psi)} \tag{39}$$

Local Mach Number Calculation

After all the corrections are applied to the static and dynamic pressure measurements the local Mach number at each boom is computed from:

$$M_j = \sqrt{\left(\frac{2}{\gamma - 1}\right)\left[\left(\frac{q_j}{Ps_j} + 1\right)^{\frac{\gamma-1}{\gamma}} - 1\right]} \qquad j = n, r, l \tag{40}$$

where the ratio of specific heats *(γ)* for air is 1.40. The average local Mach number is then computed as:

$$M_{avg} = \tfrac{1}{3}\left(M_n + M_r + M_l\right) \tag{41}$$

Free-Air Temperature and Speed of Sound Calculation

The measured temperature is converted from degrees Celsius to absolute temperature in degrees Rankine.

$$T_{abs} = \tfrac{9}{5} \cdot T_m + 32 + 459.67 \quad (^\circ\text{R}) \tag{42}$$

The free-stream air temperature is then computed from the local absolute temperature as:

$$T_\infty = \frac{T_{abs}}{1 + \left[\left(\frac{\gamma - 1}{2}\right) \cdot K \cdot M_{avg}^2\right]} \quad (^\circ\text{R}) \tag{43}$$

where the temperature recovery factor *(K)* is 0.995. The potential temperature is computed as:

$$T_\theta = T_\infty \left(\frac{P_{ref}}{Ps_n \cdot 68.9475}\right)^{2/7} \quad (^\circ\text{R}) \tag{44}$$

where the reference pressure (P_{ref}) is 1000 millibars.

The free-stream speed of sound is computed from:

$$a = \sqrt{\gamma \frac{P_o}{\rho_o} \frac{T_\infty}{T_o}} \quad \text{(fps)} \tag{45}$$

where:

$$P_o = 2116.22 \quad (\text{lb/ft}^2)$$
$$\rho_o = 0.0023769 \quad (\text{slug/ft}^3)$$
$$T_o = 518.67 \quad (^\circ\text{R})$$

The local true airspeed is computed from the local Mach number and the free-stream speed of sound.

$$Vt_{loc_j} = M_j \cdot a \quad \text{(fps)} \qquad j = n,r,l \tag{46}$$

Airplane Angular Motion Correction to Body Axis Airspeed Components

The body-axis airspeed components are computed and corrected for the airplane angular motions as:

$$u_{b_j} = Vt_{loc_j} \cos\alpha_j \cos\beta_j + \frac{\pi}{180}\left[r_m\left(y_j - y_b\right) - q_m\left(z_j - z_b\right)\right] \quad \text{(fps)} \qquad j = n,r,l \tag{47}$$

$$v_{b_j} = Vt_{loc_j} \sin\beta_j + \frac{\pi}{180}\left[p_m\left(z_j - z_b\right) - r_m\left(x_j - x_b\right)\right] \quad \text{(fps)} \qquad j = n,r,l \tag{48}$$

$$w_{b_j} = Vt_{loc_j} \sin\alpha_j \cos\beta_j + \frac{\pi}{180}\left[q_m\left(x_j - x_b\right) - p_m\left(y_j - y_b\right)\right] \quad \text{(fps)} \qquad j = n,r,l \tag{49}$$

The airplane axis x, y and z coordinates of the boom probes and body axis origin (x_b, y_b, z_b) are listed in Table 5. The angular rates (p_m, q_m, r_m) are from the mechanical gyros and are sampled at 32 times per second while the velocity parameters are sampled at 128 times per second. The angular rates are interpolated in the missing time slots (3 points between each sample). The angular rates from the mechanical gyros were selected over the LN-93 INU rates due to a dithering of the INU rate signals.

True Airspeed, Angle Of Attack and Sideslip Calculation

The true airspeed at each boom is computed as:

$$Vt_j = \sqrt{u_{b_j}^2 + v_{b_j}^2 + w_{b_j}^2} \quad \text{(fps)} \qquad j = n,r,l \tag{50}$$

The angle of attack at each boom is computed as:

$$\alpha_{t_j} = \frac{180}{\pi}\tan^{-1}\left(\frac{w_{b_j}}{u_{b_j}}\right) \quad \text{(deg)} \qquad j = n,r,l \tag{51}$$

The sideslip angle at each boom is computed as:

$$\beta_{t_j} = \frac{180}{\pi}\sin^{-1}\left(\frac{v_{b_j}}{Vt_j}\right) \quad \text{(deg)}$$
$$j = n, r, l \tag{52}$$

The average airspeed components and flow angles are then computed.

$$Vt_{avg} = \frac{1}{3}\left(Vt_n + Vt_r + Vt_l\right) \quad \text{(fps)} \tag{53}$$

$$u_{b_{avg}} = \frac{1}{3}\left(u_{bn} + u_{br} + u_{bl}\right) \quad \text{(fps)} \tag{54}$$

$$v_{b_{avg}} = \frac{1}{3}\left(v_{bn} + v_{br} + v_{bl}\right) \quad \text{(fps)} \tag{55}$$

$$w_{b_{avg}} = \frac{1}{3}\left(w_{bn} + w_{br} + w_{bl}\right) \quad \text{(fps)} \tag{56}$$

$$\alpha_{avg} = \frac{1}{3}\left(\alpha_{t_n} + \alpha_{t_r} + \alpha_{t_l}\right) \quad \text{(deg)} \tag{57}$$

$$\beta_{avg} = \frac{1}{3}\left(\beta_{t_n} + \beta_{t_r} + \beta_{t_l}\right) \quad \text{(deg)} \tag{58}$$

Calculation of Wind Components in Earth Axis System

The airspeed components are transformed from the body axis system to the Earth axis system through transformation equation:

$$\begin{pmatrix} u_{e_j} \\ v_{e_j} \\ w_{e_j} \end{pmatrix} = \mathbf{T}_{be}\begin{pmatrix} u_{b_j} \\ v_{b_j} \\ w_{b_j} \end{pmatrix} \quad \text{(fps)}$$
$$j = n, r, l, avg \tag{59}$$

where the transformation matrix ($\mathbf{T}_{be}$) is defined as:

$$\mathbf{T}_{be} = \begin{pmatrix} \cos\psi_{93}\cos\theta_{93} & \cos\psi_{93}\sin\theta_{93}\sin\phi_{93} - \sin\psi_{93}\cos\phi_{93} & \cos\psi_{93}\sin\theta_{93}\cos\phi_{93} + \sin\psi_{93}\sin\phi_{93} \\ \sin\psi_{93}\cos\theta_{93} & \sin\psi_{93}\sin\theta_{93}\sin\phi_{93} + \cos\psi_{93}\cos\phi_{93} & \sin\psi_{93}\sin\theta_{93}\cos\phi_{93} - \cos\psi_{93}\sin\phi_{93} \\ -\sin\theta_{93} & \cos\theta_{93}\sin\phi_{93} & \cos\theta_{93}\cos\phi_{93} \end{pmatrix} \tag{60}$$

The inertial wind components are computed as the difference between the airplane inertial velocity

and the measured airspeed components.

$$W_{N_j} = \dot{N} - u_{e_j} \quad \text{(fps)} \qquad j = n, r, l, avg \tag{61}$$

$$W_{E_j} = \dot{E} - v_{e_j} \quad \text{(fps)} \qquad j = n, r, l, avg \tag{62}$$

$$W_{Z_j} = -\dot{Z} - w_{e_j} \quad \text{(fps)} \qquad j = n, r, l, avg \tag{63}$$

Average Wind Speed and Direction Calculation

The average horizontal wind components are computed as:

$$W_{N_{avg}} = \frac{1}{3}\left(W_{N_l} + W_{N_n} + W_{N_r}\right) \quad \text{(fps)} \tag{64}$$

$$W_{E_{avg}} = \frac{1}{3}\left(W_{E_l} + W_{E_n} + W_{E_r}\right) \quad \text{(fps)} \tag{65}$$

The wind speed and direction are then computed from:

$$Wnd_{Spd} = 0.5925\sqrt{W_{N_{avg}}^2 + W_{E_{avg}}^2} \quad \text{(knots)} \tag{66}$$

$$Wnd_{Dir} = 180 + \tan^{-1}\left(\frac{W_{E_{avg}}}{W_{N_{avg}}}\right) \quad \text{(deg true)} \tag{67}$$

At the conclusion of the above calculations the DAS input data and selected computed parameters are recorded. Table 6 lists the recorded parameters and cross-references the equation where they are computed. The data for the next time step is read and the calculation process begins again at equation 6. This process loop is repeated until the end of the DAS file is reached.

Wake Velocity Calculation

The following process was used to derive the wake velocity measurements from the OVDRA output, the flight event information, and the GPS position data from the OV-10 and the C-130. The objective of the wake measurement flight tests was to obtain a "real world" data set for use in wake modeling analysis. The ideal data set for such analysis would be a series of instantaneous, 3-dimensional wake measurements within a fixed airmass, from initial wake rollup until final decay. However, currently there is no way to make such measurements. The OV-10 could only measure the wake velocity at 3-points in space at any instant in time. A wake measurement pass consists of 3 streams of wake velocity data collected at 128 Hz, over a 5 to 10 second period. Successive wake measurements were made in different airmass regions rather than an ideal fixed airmass. The OV-10 and C-130 inertial positions are known from differential GPS measurements collected at 1 Hz. The following process was used to translate the measured wake velocity data to an inertial-referenced frozen axis system.

Wake Coordinate System

The wake vortex axis system (X_w, Y_w), shown in figure 12, is aligned with the bearing between the OV-10 and C-130 at the time of the wake vortex encounter (t_{ref}). The origin of the coordinate system is the C-130 position when it generated the wake being measured (C-130 position at t_o).

Wake Velocity Algorithm

The wake velocity algorithm Wake_Vel must translate the OVDRA wind measurements to the wake coordinate system. Each wake measurement event has it own wake coordinate system. As noted in the previous section, the origin of the coordinate system is the C-130 position (latitude, longitude, and altitude) when it generated the measured wake event. Since the wake translates with the airmass this origin location must be iteratively determined based on the known C-130 track and OV-10 measurement location, and the average wind component determined from measurements outside the wake. The wake origin location also determines the wake age.

Filtering GPS position data. The wake velocity algorithm begins by reading and filtering the OV-10 and C-130 Ashtech differential GPS data files for a given flight. The read and filter operations are the same for both the OV-10 and C-130 data. The following data parameters are read at each time step:

t_{GPS}	GPS time, seconds
SV	Number of satellites received
$PDOP$	Dilution of Precision Parameter
Lat_N	Latitude north, degrees
Lng_W	Longitude west, degrees
HI	Geometric altitude, meters
RMS	Root mean squared position error, meters

The following criteria are used to filter poor position data from the GPS files. The data that do not meet the criteria are omitted.

$$\begin{aligned} RMS &\le 1.0 \\ PDOP &\le 4.0 \\ SV &\ge 4 \end{aligned} \tag{68}$$

For the remaining data, the GPS time is converted to Coordinated Universal Time (UTC) through:

$$t = \begin{cases} t_{GPS} - 10.0 & \text{for 1995 flights} \\ t_{GPS} - 11.0 & \text{for 1996 flights} \\ t_{GPS} - 12.0 & \text{for 1997 flights} \\ t_{GPS} - 26.7 & \text{for flight 705 (DAS time not reset)} \end{cases} \tag{69}$$

The longitude west is converted to longitude east, and the geometric altitude is converted to feet through:

$$Z = -3.281 * HI \quad \text{(ft)} \tag{70}$$

Begin wake velocity computation loop. The wake velocity computation loop begins with reading the

event data. The loop is repeated until the end of the event data is reached. The event information consists of:

t_{start}	Event start time, UTC seconds
t_{stop}	Event stop time, UTC seconds
t_{ref}	Time of vortex encounter, UTC seconds
Vrtx	Vortex identifier (L for left, R for Right) corresponding to t_{ref}
V_{wnd}	Wind speed, knots
Ψ_{wnd}	Wind direction, degrees true
Outfile	Wake_Vel output file name

Find OV-10 locations corresponding to event start, stop and reference times. The first step in the computation loop is to interpolate the 1 Hz OV-10 GPS data to find the location corresponding to t_{start}, t_{stop}, and t_{ref}. The algorithm will not interpolate between points with data dropouts. If the time interval between a pair of GPS data points is greater than 1.2 seconds, then the data between those points did not meet the dropout check criteria. An error message stating that the GPS data is invalid over the interpolation region is written and the event output file is closed. The algorithm returns to the beginning of the loop to read the next event data.

Determine when C-130 generated the wake encountered. This is the beginning of a search-loop to determine when the C-130 generated the wake encountered. The search begins at the C-130 location corresponding to t_{ref} and searches backward to find the time (t_o) when the wake encounter position (corrected for the wind drift) is closest to the C-130 track. A flowchart of the search algorithm is shown in figure 13.

$$t_o = f\left(t_{ref}, Lat_{OV_{ref}}, Lng_{OV_{ref}}, Vrtx, \Psi_{wnd}, V_{wnd}, \text{C-130 GPS data}\right) \tag{71}$$

The algorithm, as depicted, finds the nearest C-130 data point corresponding to the wake generation point. The algorithm has a second iteration loop (not depicted for clarity) which interpolates between GPS data points to find the wake origin time to the nearest tenth of a second and corresponding location (Lat_o, Lng_o, Z_o). The search algorithm also uses several functions relating range and bearing between two latitude and longitude points which are not explicitly expressed in figure 13. These functions are given below.

The range from (Lat_a, Lng_a) to (Lat_b, Lng_b) is computed as:

$$Rng = 60\frac{180}{\pi}\left[\frac{\pi}{2} + \tan^{-1}\left(\frac{-\xi}{\sqrt{1-\xi^2}}\right)\right] \quad \text{(n.mi.)} \tag{72}$$

where $\xi = \sin Lat_a \sin Lat_b + \cos Lat_a \cos Lat_b \cos(Lng_b - Lng_a)$

The bearing from (Lat_a, Lng_a) to (Lat_b, Lng_b) is computed as:

$$\Psi = \frac{180}{\pi}\left[\frac{\pi}{2} + \tan^{-1}\left(\frac{-\xi}{\sqrt{1-\xi^2}}\right)\right] \quad \text{(deg)}$$
$$\text{where } \xi = \frac{\sin Lat_b - \sin Lat_a \cos\frac{Rng}{60}}{\cos Lat_a \sin\frac{Rng}{60}} \tag{73}$$

The latitude and longitude of a point at a given range (*Rng* in nautical miles) and bearing (Ψ) from an initial location (Lat_a, Lng_a) are computed from:

$$Lat = Lat_a + \frac{Rng}{60}\cos\Psi \quad \text{(deg)} \tag{74}$$

$$Lng = Lng_a + \frac{Rng \sin\Psi}{60\cos\left(\frac{Lat + Lat_a}{2 - 2\cdot 10^{-6} Rng}\right)} \quad \text{(deg)} \tag{75}$$

Compute wake age. At the conclusion of the search for t_o the wake age is computed from:

$$\Delta t = t_{ref} - t_o \tag{76}$$

Find C-130 location corresponding to event start and stop times. The C-130 GPS data is interpolated to find its location at $t_{start} - \Delta t$ and $t_{stop} - \Delta t$. As with the OV-10 GPS interpolation, the interpolation interval is checked for validity. If the time interval between interpolation data points is greater than 1.2 seconds, then the GPS data did not meet the dropout filter criteria over that region. An error message stating that the GPS data is invalid is written and the event output file is closed. The algorithm returns to the beginning of the loop to read the next event data.

Find C-130 location at the reference time. A linear extraploation of the C-130 ground track from $t_{start} - \Delta t$ to $t_{stop} - \Delta t$ is used to compute its location at t_{ref}. The linear projection approach is used rather than interpolating the GPS data because at the end of the runs the C-130 often turns or enters a circular pattern until the OV-10 completes its wake measurements. Interpolating the GPS data for the C-130 position in such a situation will result in the wake axis system being misaligned.

Least squares linear fits of the C-130 GPS latitude and longitude as functions of time are computed from $t_{start} - \Delta t$ to $t_{stop} - \Delta t$. The projected latitude ($Lat_{C_{ref}}$) and longitude ($Lng_{C_{ref}}$) corresponding to t_{ref} are then computed from the linear fit.

Compute vortex initial location at the reference time. The vortex initial location at t_{ref} is assumed to be the left or right wing tip location of the C-130. The wing tip location at t_{ref} is computed as:

$$Lat_{tip},\ Lng_{tip} = f\left(Lat_{C_{tref}}, Lng_{C_{tref}}, \Psi_{tip}, \tfrac{1}{2}b_{C130}\right) \tag{77}$$

using equations 74 and 75, respectively; where

$$\Psi_{tip} = \begin{cases} \Psi_{C130} + 90 & , Vrtx = \text{R (right vortex)} \\ \Psi_{C130} - 90 & , Vrtx = \text{L (left vortex)} \end{cases} \tag{78}$$

and

$$\Psi_{C130} = f\left[Lat_{C130}(t_{start} - \Delta t), Lng_{C130}(t_{start} - \Delta t), Lat_{C130}(t_{stop} - \Delta t), Lng_{C130}(t_{stop} - \Delta t)\right] \tag{79}$$

from equation 73.

Compute heading of wake axis system. The bearing from the OV-10 location at t_{ref} and the C-130 tip location at t_{ref} is the heading of the wake axis system. The wake axis heading is obtained as:

$$\Psi_w = f\left(Lat_{tip}, Lng_{tip}, Lat_{OV_{ref}}, Lng_{OV_{ref}}\right) \tag{80}$$

from equation 73.

Compute Earth to Wake axis transformation matrix. The Earth to wake axis system transformation matrix elements are computed as:

$$\mathbf{T}_{ew} = \begin{pmatrix} \cos\Psi_w & \sin\Psi_w & 0 \\ -\sin\Psi_w & \cos\Psi_w & 0 \\ 0 & 0 & 1 \end{pmatrix} \tag{81}$$

Compute OV-10 INS velocity integration correction factor. The OV-10 position at each 128 Hz data record is determined by integrating the LN-93 INS velocity components over the duration of the event. An integration correction factor is then calculated that forces the position calculations to match the 1 Hz Ashtech GPS position data.

The north, east and vertical distance traveled during the event are first computed by integrating the LN-93 velocities from t_{start} to t_{stop}.

$$d_{N_{INS}} = \sum_{t_{start}}^{t_{stop}} \tfrac{1}{2}(t_i - t_{i-1})(\dot{N}_i - \dot{N}_{i-1}) \quad \text{(ft)} \tag{82}$$

$$d_{E_{INS}} = \sum_{t_{start}}^{t_{stop}} \tfrac{1}{2}(t_i - t_{i-1})(\dot{E}_i - \dot{E}_{i-1}) \quad \text{(ft)} \tag{83}$$

$$d_{Z_{INS}} = \sum_{t_{start}}^{t_{stop}} -\tfrac{1}{2}(t_i - t_{i-1})(\dot{Z}_i - \dot{Z}_{i-1}) \quad \text{(ft)} \tag{84}$$

The range and bearing from the event starting location to the stop location are then computed from equations 72 and 73, respectively.

$$Rng, \Psi = f\left(Lat_{OV_{start}}, Lng_{OV_{start}}, Lat_{OV_{stop}}, Lat_{OV_{stop}}\right) \tag{85}$$

The north, east and vertical distances based on the OV-10 Ashtech GPS data are computed as:

$$d_{N_{GPS}} = 6076.1 \cdot Rng \cdot \cos\Psi \quad \text{(ft)} \tag{86}$$

$$d_{E_{GPS}} = 6076.1 \cdot Rng \cdot \sin\Psi \quad \text{(ft)} \tag{87}$$

$$d_{Z_{GPS}} = Z_{OV_{start}} - Z_{OV_{stop}} \quad \text{(ft)} \tag{88}$$

The north, east and vertical integration correction factors are then computed.

$$Cor_j = \frac{d_{j_{GPS}} - d_{j_{INS}}}{t_{stop} - t_{start}} \qquad j = N, E, Z \tag{89}$$

Compute the event origin offset distances. The origin of the wake axis system is the location of the C-130 at t_0 (equation 71). The range and bearing from the event starting location to the C-130 initial location are computed from equations 72 and 73, respectively.

$$Rng, \Psi = f\left[Lat_{OV_{start}}, Lng_{OV_{start}}, Lat_o, Lng_o\right] \tag{90}$$

The origin-offset distances are then computed as:

$$d_{N_o} = 6076.1 \cdot Rng \cdot \cos\Psi \quad \text{(ft)} \tag{91}$$

$$d_{E_o} = 6076.1 \cdot Rng \cdot \sin\Psi \quad \text{(ft)} \tag{92}$$

$$d_{Z_o} = Z_{OV_{start}} - Z_o \quad \text{(ft)} \tag{93}$$

Compute OV-10 position and wind velocities in the wake axis system. The OV-10 position in the wake axis system is computed at each data record by integrating the INS velocities with the integration correction factors and origin offset. The measured wind velocities are also transformed to the wake axis system.

The INS velocity components are integrated with the correction factors and origin offsets for $t_{start} \le t_i \le t_{stop}$:

$$d_{N_i} = d_{N_o} + Cor_N\left(t_i - t_{start}\right) + \sum_{j=i_{start}}^{i} \frac{1}{2}\left(t_j - t_{j-1}\right)\left(\dot{N}_j - \dot{N}_{j-1}\right) \quad \text{(ft)} \tag{94}$$

$$d_{E_i} = d_{E_o} + Cor_E\left(t_i - t_{start}\right) + \sum_{j=i_{start}}^{i} \frac{1}{2}\left(t_j - t_{j-1}\right)\left(\dot{E}_j - \dot{E}_{j-1}\right) \quad \text{(ft)} \tag{95}$$

$$d_{Z_i} = d_{Z_o} + Cor_Z\left(t_i - t_{start}\right) + \sum_{j=i_{start}}^{i} -\frac{1}{2}\left(t_j - t_{j-1}\right)\left(\dot{Z}_j - \dot{Z}_{j-1}\right) \quad \text{(ft)} \tag{96}$$

where i and i_{start} are the data array indices corresponding to t_i and t_{start}, respectively.

The distance components are then transformed to the wake axis system yielding the coordinates of the OV-10 body axis origin in the wake axis system.

$$\begin{pmatrix} x_{o_w} \\ y_{o_w} \\ z_{o_w} \end{pmatrix}_i = \mathbf{T}_{ew} \begin{pmatrix} d_N \\ d_E \\ d_Z \end{pmatrix}_i \quad \text{(ft)} \tag{97}$$

The boom coordinates in the Earth axis system are computed.

$$\begin{pmatrix} x_{j_e} \\ y_{j_e} \\ z_{j_e} \end{pmatrix}_i = \mathbf{T}_{be_i} \begin{pmatrix} x_j - x_b \\ y_j - y_b \\ z_j - z_b \end{pmatrix} \quad \text{(ft)} \qquad j = r, l, n \tag{98}$$

where the components of the $\mathbf{T}_{be}$ matrix are obtained from the OVDRA file at each time step.

The boom coordinates and wind measurements are then transformed to the wake axis system.

$$\begin{pmatrix} x_{j_w} \\ y_{j_w} \\ z_{j_w} \end{pmatrix}_i = \begin{pmatrix} x_{o_w} \\ y_{o_w} \\ z_{o_w} \end{pmatrix}_i + \mathbf{T}_{ew} \begin{pmatrix} x_{j_e} \\ y_{j_e} \\ z_{j_e} \end{pmatrix}_i \quad \text{(ft)} \qquad j = r, l, n \tag{99}$$

$$\begin{pmatrix} u_{j_w} \\ v_{j_w} \\ w_{j_w} \end{pmatrix}_i = \mathbf{T}_{ew} \begin{pmatrix} W_{N_j} \\ W_{E_j} \\ W_{Z_j} \end{pmatrix}_i \quad \text{(fps)} \qquad j = r, l, n \tag{100}$$

Wake position correction for wind drift. This correction is made in an effort to obtain an instantaneous sample of the wake velocity flow-field. Since a wake measurement pass requires a number of seconds to complete, the measurement positions must be corrected to account for the drift of the wake over the measurement period.

First, the average wind, which is one of the inputs to the Wake_Vel algorithm, is translated to the wake axis system.

$$\begin{pmatrix} Wnd_x \\ Wnd_y \\ 0 \end{pmatrix} = \mathbf{T}_{ew} \begin{pmatrix} Wnd_N \\ Wnd_E \\ 0 \end{pmatrix} \quad \text{(fps)} \tag{101}$$

where

$$\begin{pmatrix} Wnd_N \\ Wnd_E \end{pmatrix} = 1.688 \cdot V_{wnd} \cdot \begin{pmatrix} \cos\left(\Psi_{wnd} - 180\right) \\ \sin\left(\Psi_{wnd} - 180\right) \end{pmatrix} \quad \text{(fps)} \tag{102}$$

Each point in the measurement pass is then corrected for wind drift relative to the position at t_{ref} .

$$\begin{pmatrix} x_{j_w} \\ y_{j_w} \end{pmatrix}_i = \begin{pmatrix} x_{j_w} \\ y_{j_w} \end{pmatrix}_i - \begin{pmatrix} drift_x \\ drift_y \end{pmatrix} \quad \text{(ft)} \tag{103}$$
$$j = r, l, n$$

where

$$\begin{pmatrix} drift_x \\ drift_y \end{pmatrix} = \left(t_i - t_{ref}\right) \begin{pmatrix} Wnd_x \\ Wnd_y \end{pmatrix} \quad \text{(ft)} \tag{104}$$

Write wake velocities and positions to output file. The wake velocities and positions at each boom are written to the output file *Outfile*.

Closing Remarks

This paper has described and documented the flight-data reduction process for a series of flight tests that were conducted to measure airplane wake and atmospheric state information. A specially instrumented North American Rockwell OV-10 airplane was used to measure the wake and atmospheric conditions. A Lockheed C-130 airplane was used to generate the wake. An integrated database has been compiled for wake characterization and validation of wake vortex computational models.

References

1 Vicroy, Dan D.; Vijgen, Paul M.; Reimer, Heidi M.; Gallegos, Joey L.; and Spalart Philippe R.: "Recent NASA Wake-Vortex Flight Tests, Flow-Physics Database and Wake-Development Analysis," AIAA/SAE 1998 World Aviation Conference, AIAA/SAE 98-5592, September 1998.

2. Stuever, R. A.; Stewart, E. C.; and Rivers, R. A.: "Overview of the Preparation and Use of an OV-10 Aircraft for Wake Vortex Flight Experiments," AIAA 95-3935, September 1995.

3. Richardson, Norman R.: "Dynamic and Static Wind-Tunnel Tests of a Flow-Direction Vane," NASA TN D-6193, April 1971.

4. Taback, Isreal: "The Response of Pressure Measuring Systems to Oscillating Pressures," NACA TN-1819, February 1949.

5. Gracey, William: “Measurement of Aircraft Speed and Altitude,” NASA RP-1046, May 1980.

Table 1. Data acquisition system recorded data parameters.

Data #	Symbol	Database Name	Units	Sample Rate (Hz)	Description
0		*TIME*	seconds	128	Time
1		*FWDVIB*	Gs	128	Nose boom vibrometer
2		*LTVIB*	Gs	128	Left boom vibrometer
3	q_l'	*LT_AIRSP*	psi	128	Left boom raw dynamic pressure measurement
4	α_{Vn_l}	*LT_ALPHVN*	deg	128	Left boom raw angle of attack measurement
5	β_{Vn_l}	*LT_BETAVN*	deg	128	Left boom raw flank angle measurement
6		*NSVIB*	Gs	128	Nose boom vibrometer
7		*P3*	psi	128	Nose boom center hole pressure
8	$\Delta P_{3\alpha 1}'$	*P3_PA1*	psi	128	Nose boom 5-hole probe pressure difference measurement
9	$\Delta P_{3\beta 1}'$	*P3_PB1*	psi	128	Nose boom 5-hole probe pressure difference measurement
10	q_n'	*P3_PS*	psi	128	Nose boom dynamic pressure measurement
11	$\Delta P_{\alpha 12}'$	*PA1_PA2*	psi	128	Nose boom angle of attack pressure difference measurement
12	$\Delta P_{\beta 12}'$	*PB1_PB2*	psi	128	Nose boom sideslip angle pressure difference measurement
13	Ps_n'	*PS*	psi	128	Nose boom static pressure measurement
14		*RTVIB*	Gs	128	Right boom vibrometer
15	q_r'	*RT_AIRSP*	psi	128	Right boom raw dynamic pressure measurement
16	α_{Vn_r}	*RT_ALPHVN*	deg	128	Right boom raw angle of attack measurement
17	β_{Vn_r}	*RT_BETAVN*	deg	128	Right boom raw flank angle measurement
18		*TIMEDAYS*	days	128	Day
19		*TIMEHRS*	hours	128	Hour
20		*TIMEMIN*	minutes	128	Minute
21		*TIMESEC*	seconds	128	Second
22		*TIMEMILSEC*	millsecs	128	Millisecond
23		*AIRTMP_ADC*	deg K	8	Outside air temperature from air-data computer
24		*CAL_AS_ADC*	knots	8	Calibrated airspeed from air-data computer
25		*DEWPTTEMP*	deg C	32	Dew-point temperature

Table 1. Continued.

Data #	Symbol	Database Name	Units	Sample Rate (Hz)	Description
26		*ELEVDEFL*	deg	32	Elevator deflection (+ trailing edge up)
27		*EVENTMARK*	on / off	32	Event marker
28	$\dot{E}$	*E_W_VEL93*	ft/sec	32	Inertial velocity east from LN-93 INS
29		*HEADING*	deg	32	True heading from mechanical gyro
30		*INERTALT93*	ft	32	Inertial altitude from LN-93 INS
31		*LATACC*	Gs	32	Lateral acceleration from accelerometer
32		*LONGACC*	Gs	32	Longitudinal acceleration from accelerometer
33		*LT_AILDEFL*	deg	32	Left aileron deflection (+ trailing edge up)
34		*LT_PAL05*	psi	32	Left boom static pressure measurement (0 to 5000 ft)
35		*LT_PAL510*	psi	32	Left boom static pressure measurement (5000 to 10000 ft)
36	$Ps_l{}'$	*LT_PRESAL*	psi	32	Left boom static pressure measurement (0 to 15000 ft)
37		*LT_RUDDEFL*	deg	32	Left rudder deflection (+ trailing edge left)
38		*MACHNO_ADC*	Mach	8	Mach number from air-data computer
39		*NORMACC*	Gs	32	Normal acceleration from accelerometer
40	$\dot{N}$	*N_S_VEL93*	ft/sec	32	Inertial velocity north from LN-93 INS
41	$T_m{}'$	*OUTAIRTEMP*	deg C	32	Total-air-temperature from TAT probes
42		*PITCHATT*	deg	32	Pitch angle from mechanical gyro
43	θ_{93}	*PITCHATT93*	deg	32	Pitch angle from LN-93 INS
44	$q_m{}'$	*PITCHRAT*	deg/sec	32	Pitch rate from mechanical gyro
45		*PITCHRAT93*	deg/sec	32	Pitch rate from LN-93 INS
46		*PLATAZ93*	deg	32	INS platform azimuth from LN-93
47		*PRESAL_ADC*	psi	8	Static pressure from air-data computer
48		*ROLLATT*	deg	32	Roll angle from mechanical gyro
49	ϕ_{93}	*ROLLATT93*	deg	32	Roll angle from LN-93 INS
50		*ROLLRATE93*	deg/sec	32	Roll rate from LN-93 INS
51		*ROLLRATHI*	deg/sec	32	Roll rate from high range mechanical gyro
52	$p_m{}'$	*ROLLRATLOW*	deg/sec	32	Roll rate from low range mechanical gyro
53		*RT_AILDEFL*	deg	32	Right aileron deflection (+ trailing edge down)
54	$Ps_r{}'$	*RT_PRESAL*	psi	32	Right boom static pressure measurement
55		*TRUEAS_ADC*	knots	8	True airspeed from air-data computer

Table 1. Concluded.

Data #	Symbol	Database Name	Units	Sample Rate (Hz)	Description
56		*TRUEAS_93*	knots	32	True airspeed from LN-93 INS
57	ψ_{93}	*TRUEHEAD93*	deg	32	True heading from LN-93 INS
58	$\dot{Z}$	*VERTVEL93*	ft/sec	32	Inertial velocity up from LN-93 INS
59	$r_m{}'$	*YAWRAT*	deg/sec	32	Yaw rate from yaw gyro
60		*YAWRATE93*	deg/sec	32	Yaw rate from LN-93 INS
61		*XVEL93*	ft/sec	32	X inertial velocity from LN-93 INS in the navigation reference frame
62		*YVEL93*	ft/sec	32	Y inertial velocity from LN-93 INS in the navigation reference frame
63		*ZVEL93*	ft/sec	32	Z inertial velocity from LN-93 INS in the navigation reference frame
64		*ALIGN_STAT*	12 = done		LN_93 alignment status flag
65		*ALTDIFFGPS*	feet	8	
66		*ALTGPS*	feet	8	Altitude from Honeywell GPS. Over-sampled, refreshed at 1/sec
67		*CARGOTEMP1*	deg F	8	Cargo bay temperature
68		*GARGOTEMP2*	deg F	8	Cargo bay temperature
69		*CH1_CNR*	dB	8	Honeywell GPS channel 1 strength. Over-sampled, refreshed at 1/sec
70		*CH2_CNR*	dB	8	Honeywell GPS channel 2 strength. Over-sampled, refreshed at 1/sec
71		*CH3_CNR*	dB	8	Honeywell GPS channel 3 strength. Over-sampled, refreshed at 1/sec
72		*CH4_CNR*	dB	8	Honeywell GPS channel 4 strength. Over-sampled, refreshed at 1/sec
73		*CH5_CNR*	dB	8	Honeywell GPS channel 5 strength. Over-sampled, refreshed at 1/sec
74		*CRVCR_MODE*		8	Over-sampled, refreshed at 1/sec
75		*DATAON*	on / off	8	Data switch position
76		*DRIFTANG93*	deg	8	Drift angle from LN-93 INS
116		*LAT93*	deg	8	Latitude from LN-93 INS Note: Over-sampled, refreshed at 4/sec
117		*LATGPS*	deg	8	Latitude from Honeywell GPS. Over-sampled, refreshed at 1/sec
118		*LONG93*	deg	8	Longitude from LN-93 INS Over-sampled, refreshed at 4/sec
119		*LONGGPS*	deg	8	Longitude from Honeywell GPS. Over-sampled, refreshed at 1/sec
120		*VELE_GPS*	ft/sec	8	Velocity east from Honeywell GPS. Over-sampled, refreshed at 1/sec
121		*VELN_GPS*	ft/sec	8	Velocity north from Honeywell GPS. Over-sampled, refreshed at 1/sec
122		*VELUP_GPS*	ft/sec	8	Velocity up from Honeywell GPS. Over-sampled, refreshed at 1/sec

Table 2. Calibration coefficient values.

Symbol	Default Value	Units	Description
k_{α_r}	0.8223	-	Linear slope of right vane angle of attack calibration
k_{η_r}	1.0073	-	Linear slope of right flank angle vane calibration
k_{α_l}	0.8363	-	Linear slope of left vane angle of attack calibration
k_{η_l}	0.9999	-	Linear slope of left flank angle vane calibration
b_{α_r}	-1.7568	deg	Calibration bias for right angle of attack vane
b_{η_r}	1.4417	deg	Calibration bias for right flank angle vane measurement
b_{α_l}	-0.8308	deg	Calibration bias for left angle of attack vane
b_{η_l}	-0.1695	deg	Calibration bias for left flank angle vane measurement
k_{α_n}	0.8002	-	Linear slope of the nose boom angle of attack calibration
k_{β_n}	0.9183	-	Linear slope of the nose boom side-slip calibration
b_{α_n}	0.4420	deg	Bias term of the nose boom angle of attack calibration
b_{β_n}	0.5686	deg	Bias term of the nose boom side-slip calibration
$k_{\Delta Pqn}$	0.08849	-	Slope of nose boom position error correction curve for zero side-slip
$b_{\Delta Pqn}$	-0.00752	psi	Y-intercept of nose boom position error correction curve for zero side-slip
$k_{\Delta Pqr}$	0.014903	-	Slope of right boom position error correction curve for zero side-slip
$b_{\Delta Pqr}$	-0.00236	psi	Y-intercept of right boom position error correction curve for zero side-slip
$k_{\Delta Pql}$	0.018634	-	Slope of left boom position error correction curve for zero side-slip
$b_{\Delta Pql}$	-0.00362	psi	Y-intercept of left boom position error correction curve for zero side-slip
$k_{\Delta Pq\beta_n}$	-0.00294	psi/deg	Slope of nose boom position error correction due to side-slip
$k_{\Delta Pq\beta_1}$	0.000661	psi/deg	Slope of wing boom position error correction due to side-slip
$k_{\Delta Pq\beta_2}$	0.000670	psi/deg	Slope of wing boom position error correction due to side-slip
$b_{\Delta Pq\beta_n}$	0.010261	psi	Y-intercept of nose boom position error correction curve due to side-slip
$b_{\Delta Pq\beta_1}$	0	psi	Y-intercept of wing boom position error correction curve due to side-slip
$b_{\Delta Pq\beta_2}$	0	psi	Y-intercept of wing boom position error correction curve due to side-slip

Table 3. NACA pitot probe static pressure calibration coefficient (C_s) values.

	|β|, deg								
α, deg	0	5	10	15	20	25	30	35	40
-40	0.2976	0.3071	0.3245	0.3403	0.4263	0.5335	0.6680	0.6153	0.5247
-38	0.2673	0.2761	0.2922	0.3088	0.3771	0.4839	0.6534	0.6481	0.5440
-36	0.2482	0.2562	0.2709	0.2880	0.3407	0.4473	0.6194	0.6651	0.5635
-34	0.2325	0.2405	0.2554	0.2729	0.3147	0.4121	0.5817	0.6648	0.5833
-32	0.2158	0.2248	0.2411	0.2594	0.2963	0.3717	0.5456	0.6387	0.6027
-30	0.1960	0.2067	0.2253	0.2453	0.2815	0.3360	0.4811	0.6077	0.6181
-28	0.1763	0.1885	0.2127	0.2348	0.2723	0.3203	0.4270	0.5716	0.6262
-26	0.1518	0.1648	0.1981	0.2221	0.2617	0.3104	0.3892	0.5455	0.6291
-24	0.1308	0.1439	0.1785	0.2040	0.2458	0.2976	0.3600	0.5149	0.6252
-22	0.1144	0.1272	0.1564	0.1843	0.2277	0.2827	0.3366	0.4814	0.6151
-20	0.0942	0.1065	0.1372	0.1697	0.2151	0.2729	0.3235	0.4020	0.6006
-18	0.0553	0.0673	0.1190	0.1599	0.2084	0.2685	0.3182	0.3646	0.5839
-16	0.0366	0.0482	0.0975	0.1499	0.2014	0.2634	0.3127	0.3588	0.5676
-14	0.0264	0.0378	0.0746	0.1348	0.1878	0.2513	0.3025	0.3493	0.5538
-12	0.0195	0.0307	0.0619	0.1258	0.1791	0.2437	0.3005	0.3465	0.5424
-10	0.0143	0.0252	0.0539	0.1190	0.1725	0.2375	0.3008	0.3479	0.5332
-8	0.0097	0.0204	0.0495	0.1150	0.1688	0.2337	0.3012	0.3511	0.5258
-6	0.0062	0.0167	0.0477	0.1130	0.1675	0.2318	0.3010	0.3544	0.5197
-4	0.0033	0.0138	0.0467	0.1115	0.1666	0.2303	0.2995	0.3560	0.5148
-2	0.0011	0.0117	0.0459	0.1101	0.1656	0.2287	0.2971	0.3554	0.5109
0	0.0000	0.0106	0.0452	0.1091	0.1648	0.2276	0.2949	0.3542	0.5081
2	0.0000	0.0108	0.0446	0.1083	0.1640	0.2269	0.2935	0.3536	0.5064
4	0.0000	0.0110	0.0431	0.1067	0.1624	0.2255	0.2919	0.3533	0.5058
6	0.0000	0.0112	0.0411	0.1047	0.1604	0.2240	0.2908	0.3545	0.5065
8	0.0011	0.0122	0.0412	0.1045	0.1603	0.2243	0.2919	0.3594	0.5085
10	0.0022	0.0124	0.0419	0.1043	0.1605	0.2238	0.2926	0.3652	0.5122
12	0.0040	0.0127	0.0437	0.1042	0.1611	0.2220	0.2924	0.3710	0.5183
14	0.0066	0.0145	0.0472	0.1046	0.1623	0.2217	0.2941	0.3789	0.5267
16	0.0098	0.0187	0.0528	0.1058	0.1644	0.2252	0.2998	0.3908	0.5350
18	0.0136	0.0243	0.0592	0.1083	0.1678	0.2307	0.3080	0.4044	0.5408
20	0.0182	0.0302	0.0655	0.1126	0.1727	0.2364	0.3166	0.4173	0.5447
22	0.0236	0.0362	0.0716	0.1182	0.1788	0.2415	0.3254	0.4284	0.5476
24	0.0290	0.0421	0.0772	0.1240	0.1848	0.2457	0.3337	0.4369	0.5507
26	0.0337	0.0472	0.0819	0.1292	0.1901	0.2499	0.3421	0.4443	0.5552
28	0.0379	0.0514	0.0857	0.1340	0.1948	0.2560	0.3516	0.4531	0.5607
30	0.0421	0.0549	0.0888	0.1383	0.1989	0.2652	0.3629	0.4581	0.5608
32	0.0454	0.0566	0.0901	0.1412	0.2017	0.2750	0.3738	0.4665	0.5506
34	0.0471	0.0565	0.0897	0.1428	0.2031	0.2836	0.3828	0.4821	0.5355
36	0.0478	0.0563	0.0895	0.1447	0.2049	0.2910	0.3903	0.4829	0.5221
38	0.0482	0.0574	0.0908	0.1482	0.2085	0.2990	0.3986	0.4757	0.5109
40	0.0489	0.0598	0.0934	0.1534	0.2138	0.3088	0.4084	0.4583	0.5007

Table 4. NACA pitot probe dynamic pressure calibration coefficient (C_q) values.

	|β|, deg								
α, deg	0	5	10	15	20	25	30	35	40
-40	0.0440	0.0473	0.0489	0.0604	0.0366	0.0147	-0.0159	0.1368	0.3529
-38	0.0129	0.0118	0.0148	0.0249	0.0118	-0.0108	-0.0764	0.0299	0.2597
-36	-0.0183	-0.0201	-0.0160	-0.0068	-0.0110	-0.0358	-0.1039	-0.0473	0.1799
-34	-0.0477	-0.0507	-0.0475	-0.0391	-0.0381	-0.0587	-0.1242	-0.1038	0.1032
-32	-0.0705	-0.0755	-0.0749	-0.0676	-0.0663	-0.0728	-0.1432	-0.1308	0.0300
-30	-0.0835	-0.0911	-0.0946	-0.0894	-0.0907	-0.0857	-0.1302	-0.1485	-0.0351
-28	-0.0937	-0.1034	-0.1144	-0.1127	-0.1174	-0.1143	-0.1280	-0.1614	-0.0936
-26	-0.0911	-0.1021	-0.1242	-0.1269	-0.1356	-0.1387	-0.1372	-0.1806	-0.1424
-24	-0.0851	-0.0966	-0.1219	-0.1299	-0.1430	-0.1525	-0.1462	-0.1894	-0.1776
-22	-0.0804	-0.0919	-0.1133	-0.1289	-0.1466	-0.1615	-0.1560	-0.1948	-0.2043
-20	-0.0690	-0.0803	-0.1044	-0.1282	-0.1520	-0.1719	-0.1698	-0.1549	-0.2238
-18	-0.0366	-0.0478	-0.0940	-0.1275	-0.1587	-0.1840	-0.1859	-0.1558	-0.2389
-16	-0.0230	-0.0340	-0.0787	-0.1247	-0.1623	-0.1934	-0.1983	-0.1752	-0.2505
-14	-0.0169	-0.0277	-0.0606	-0.1154	-0.1573	-0.1938	-0.2034	-0.1822	-0.2583
-12	-0.0130	-0.0239	-0.0519	-0.1113	-0.1557	-0.1968	-0.2149	-0.1949	-0.2674
-10	-0.0101	-0.0207	-0.0468	-0.1082	-0.1546	-0.1989	-0.2262	-0.2106	-0.2773
-8	-0.0071	-0.0177	-0.0447	-0.1070	-0.1551	-0.2015	-0.2356	-0.2263	-0.2866
-6	-0.0048	-0.0152	-0.0446	-0.1070	-0.1568	-0.2044	-0.2428	-0.2401	-0.2947
-4	-0.0026	-0.0129	-0.0445	-0.1068	-0.1578	-0.2063	-0.2471	-0.2502	-0.3014
-2	-0.0008	-0.0112	-0.0443	-0.1064	-0.1582	-0.2074	-0.2495	-0.2566	-0.3069
0	0.0000	-0.0104	-0.0441	-0.1060	-0.1582	-0.2086	-0.2515	-0.2612	-0.3117
2	0.0000	-0.0106	-0.0436	-0.1053	-0.1576	-0.2094	-0.2532	-0.2647	-0.3154
4	0.0000	-0.0108	-0.0421	-0.1036	-0.1559	-0.2092	-0.2539	-0.2671	-0.3184
6	0.0000	-0.0110	-0.0402	-0.1016	-0.1538	-0.2086	-0.2541	-0.2695	-0.3208
8	-0.0011	-0.0120	-0.0402	-0.1014	-0.1537	-0.2093	-0.2556	-0.2741	-0.3227
10	-0.0021	-0.0122	-0.0409	-0.1012	-0.1538	-0.2087	-0.2558	-0.2780	-0.3247
12	-0.0038	-0.0124	-0.0426	-0.1011	-0.1542	-0.2062	-0.2539	-0.2802	-0.3271
14	-0.0063	-0.0140	-0.0460	-0.1014	-0.1551	-0.2046	-0.2528	-0.2828	-0.3299
16	-0.0092	-0.0180	-0.0512	-0.1022	-0.1564	-0.2061	-0.2548	-0.2877	-0.3307
18	-0.0127	-0.0233	-0.0573	-0.1040	-0.1586	-0.2093	-0.2582	-0.2928	-0.3273
20	-0.0170	-0.0288	-0.0630	-0.1072	-0.1617	-0.2119	-0.2607	-0.2955	-0.3201
22	-0.0220	-0.0344	-0.0684	-0.1114	-0.1653	-0.2129	-0.2617	-0.2947	-0.3100
24	-0.0268	-0.0396	-0.0730	-0.1152	-0.1678	-0.2116	-0.2601	-0.2896	-0.2982
26	-0.0305	-0.0437	-0.0762	-0.1178	-0.1686	-0.2083	-0.2561	-0.2814	-0.2856
28	-0.0332	-0.0464	-0.0778	-0.1191	-0.1674	-0.2037	-0.2499	-0.2717	-0.2710
30	-0.0349	-0.0473	-0.0773	-0.1186	-0.1636	-0.1981	-0.2415	-0.2546	-0.2472
32	-0.0339	-0.0444	-0.0729	-0.1142	-0.1551	-0.1899	-0.2299	-0.2381	-0.2101
34	-0.0298	-0.0380	-0.0650	-0.1048	-0.1404	-0.1778	-0.2144	-0.2269	-0.1661
36	-0.0224	-0.0289	-0.0544	-0.0925	-0.1217	-0.1619	-0.1959	-0.1992	-0.1221
38	-0.0104	-0.0161	-0.0402	-0.0772	-0.1016	-0.1441	-0.1768	-0.1622	-0.0788
40	0.0086	0.0030	-0.0198	-0.0561	-0.0775	-0.1222	-0.1541	-0.1098	-0.0315

Table 5. Airplane axis coordinates of system components.

x, ft	*y*, ft	*z*, ft	Description
-6.3675	19.7242	-2.6875	right boom
-6.3658	-19.7242	-2.6875	left boom tip
5.6108	2.1308	0.6292	nose boom tip
-14.5833	1.2083	0.5779	body axis origin (x_b, y_b, z_b)

Table 6. OVDRA calculated and recorded parameters.

Symbol	Units	Eqn #	Description
α_r	deg	22	Right boom local angle of attack
α_l	deg	23	Left boom local angle of attack
α_n	deg	24	Nose boom local angle of attack
η_r	deg	25	Right boom flank angle
η_l	deg	26	Left boom flank angle
β_n	deg	28	Nose boom local sideslip angle
q_r	psi	38	Right boom dynamic pressure
q_l	psi	38	Left boom dynamic pressure
q_n	psi	39	Nose boom dynamic pressure
Ps_r	psi	36	Right boom static pressure
Ps_l	psi	36	Left boom static pressure
Ps_n	psi	37	Nose boom static pressure
M_r	-	40	Right boom local Mach number
M_l	-	40	Left boom local Mach number
M_n	-	40	Nose boom local Mach number
T_{abs}	°R	42	Local absolute temperature
T_∞	°R	43	Local free-stream air temperature
T_θ	°R	44	Potential temperature
a	ft/sec	45	Local speed of sound
Vt_{loc_r}	ft/sec	46	Right boom local true airspeed
Vt_{loc_l}	ft/sec	46	Left boom local true airspeed
Vt_{loc_n}	ft/sec	46	Nose boom local true airspeed
β_r	deg	27	Right boom local sideslip angle
β_l	deg	27	Left boom local sideslip angle
u_{b_r}	ft/sec	47	Right boom body axis longitudinal airspeed
u_{b_l}	ft/sec	47	Left boom body axis longitudinal airspeed
u_{b_n}	ft/sec	47	Nose boom body axis longitudinal airspeed

Table 6. Continued.

Symbol	Units	Eqn #	Description
v_{b_r}	ft/sec	48	Right boom body axis lateral airspeed
v_{b_l}	ft/sec	48	Left boom body axis lateral airspeed
v_{b_n}	ft/sec	48	Nose boom body axis lateral airspeed
w_{b_r}	ft/sec	49	Right boom body axis vertical airspeed
w_{b_l}	ft/sec	49	Left boom body axis vertical airspeed
w_{b_n}	ft/sec	49	Nose boom body axis vertical airspeed
Vt_r	ft/sec	50	Right boom true airspeed
Vt_l	ft/sec	50	Left boom true airspeed
Vt_n	ft/sec	50	Nose boom true airspeed
α_{t_r}	deg	51	Right boom angle of attack
α_{t_l}	deg	51	Left boom angle of attack
α_{t_n}	deg	51	Nose boom angle of attack
β_{t_r}	deg	52	Right boom sideslip angle
β_{t_l}	deg	52	Left boom sideslip angle
β_{t_n}	deg	52	Nose boom sideslip angle
Vt_{avg}	ft/sec	53	Average true airspeed
$u_{b_{avg}}$	ft/sec	54	Average body axis longitudinal airspeed
$v_{b_{avg}}$	ft/sec	55	Average body axis lateral airspeed
$w_{b_{avg}}$	ft/sec	56	Average body axis vertical airspeed
α_{avg}	deg	57	Average angle of attack
β_{avg}	deg	58	Average sideslip angle
$\mathbf{T}_{be}(1,1)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(1,2)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(1,3)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(2,1)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(2,2)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(2,3)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(3,1)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(3,2)$	-	60	Body to Earth axis transformation matrix element
$\mathbf{T}_{be}(3,3)$	-	60	Body to Earth axis transformation matrix element
W_{Nr}	ft/sec	61	Right boom northerly wind velocity
W_{Er}	ft/sec	62	Right boom easterly wind velocity
W_{Zr}	ft/sec	63	Right boom vertical wind velocity

Table 6. Concluded.

Symbol	Units	Eqn #	Description
W_{Nl}	ft/sec	61	Left boom northerly wind velocity
W_{El}	ft/sec	62	Left boom easterly wind velocity
W_{Zl}	ft/sec	63	Left boom vertical wind velocity
W_{Nn}	ft/sec	61	Nose boom northerly wind velocity
W_{En}	ft/sec	62	Nose boom easterly wind velocity
W_{Zn}	ft/sec	63	Nose boom vertical wind velocity
$W_{N\,avg}$	ft/sec	61	Average northerly wind velocity
$W_{E\,avg}$	ft/sec	62	Average easterly wind velocity
$W_{Z\,avg}$	ft/sec	63	Average vertical wind velocity
V_{wnd}	knots	66	Average wind speed
Ψ_{wnd}	deg	67	Average wind direction in degrees true



Figure 1. - Wake measurement flight test setup.

Figure 2. - C-130 wake generator airplane.



Figure 3. - OV-10 major instrumentation systems



Figure 4. - OV-10 tail video of wake measurement.



(a) Pallet outside of cargo bay.



(b) Pallet installed for flight.

Figure 5. – Data acquisition system research pallet.



Figure 6. – Research equipment in the forward cargo-bay area.



Figure 7. – Right boom NACA pitot probe with angle of attack and sideslip vanes.



Figure 8. – Nose boom 5-hole probe.



Figure 9. – Flight data reduction process.



Figure 10. – Airplane and body axis systems.



Figure 11. – Euler angles with body and inertial axis systems.



Figure 12. - Wake axis system



Figure 13. Flowchart of wake origin calculation.



Figure 13. Concluded.

Appendix A – OV-10 Airspeed Calibration

The objective of the OV-10 airspeed calibration was to determine the position-error pressure corrections and the angle-of-attack and sideslip calibration for the three booms. The airspeed calibration flights were Flight 613 flown on September 24, 1996 and Flight 614 flown on November 13, 1996. The position error corrections for the left, right and nose boom were computed in a similar manner as the "camera method" described in reference 5. The difference between the method outlined here and the camera method was that the airplane altitude was determined from differential GPS measurements rather than photographically.

Flight Test Procedure

The basic test procedure involved flying a series of steady, low altitude, level passes at different airspeeds and sideslip angles. A row of 140-foot tall light towers at Langley Airforce Base (LAFB) served as a visual reference for the level passes. After every two or three low altitude passes the OV-10 would land and collect static surface data such as temperature, pressure and wind measurements. Pre- and post-flight instrument calibration data and in-flight steady trim data were also collected to determine instrumentation bias values. The data from the OV-10 experimental data system was reduced from 128 Hz to 1 Hz using a one-second-averaging interval.

Computing Reference Values

The first step in determining the calibration corrections is to compute the reference values from which the measured values are calibrated. This basically involves extrapolating surface measurements to the pass altitude based on a measured lapse rate.

Reference Angle of Attack and Sideslip Calculation

The wind velocity components during the pass must be determined to compute the reference sideslip and angle of attack. The LAFB surface winds, which were measured 12 feet above the runway, were recorded throughout each flight. Figure A1 shows the surface wind time history for both flights. The numerous takeoffs and landings throughout the flight provided a time history of the wind change with altitude. The change in the wind speed and direction with altitude was computed for each takeoff and landing through a linear fit of the measured winds from 8 to 16 feet and from 120 to 160 feet above the runway. The assumption here is that although the magnitude of OV-10 wind velocity and direction measurements were not yet calibrated and therefore not valid, the measured change of the wind velocity and direction were essentially correct. The time histories of the computed wind gradients for both flights are shown in figure A2.

The reference wind speed and direction for a given pass was computed through a linear interpolation of the surface wind speed and direction and the altitude-gradients as a function of the pass time and altitude. The altitudes were determined from the differential Ashtech GPS measurements.

$$V_{wnd}(t_{pass}) = \frac{dV_{wnd}}{dh}(t_{pass}) \cdot \left(h_{pass} - h_{grnd}\right) + V_{wnd_{grnd}}(t_{pass}) \quad \text{(knots)} \tag{A1}$$

$$\Psi_{wnd}(t_{pass}) = \frac{d\Psi_{wnd}}{dh}(t_{pass}) \cdot \left(h_{pass} - h_{grnd}\right) + \Psi_{wnd_{grnd}}(t_{pass}) \quad \text{(deg. magnetic)} \tag{A2}$$

The inertial wind components are computed from the wind direction and speed through:

$$W_N = -1.688\, V_{wnd} \cos\left(\Psi_{wnd_{mag}} - Mag_{var} \right) \quad \text{(fps)} \tag{A3}$$

$$W_E = -1.688\, V_{wnd} \sin\left(\Psi_{wnd_{mag}} - Mag_{var} \right) \quad \text{(fps)} \tag{A4}$$

$$W_Z = 0 \quad \text{(fps)} \tag{A5}$$

where the magnetic variation $\left(Mag_{var}\right)$ at the test site was 9.23 degrees west.

The reference true airspeed was computed as:

$$Vt_{ref} = \sqrt{\left(\dot{N} - W_N\right)^2 + \left(\dot{E} - W_E\right)^2 + \left(-\dot{Z} - W_Z\right)^2} \quad \text{(fps)} \tag{A6}$$

The air-mass-relative body-axis velocity components were computed from:

$$\begin{pmatrix} u_{b_{ref}} \\ v_{b_{ref}} \\ w_{b_{ref}} \end{pmatrix} = \mathbf{T}_{be}^{-1} \begin{pmatrix} \dot{N} - W_N \\ \dot{E} - W_E \\ -\dot{Z} - W_Z \end{pmatrix} \quad \text{(fps)} \tag{A7}$$

where $\mathbf{T}_{be}$ is defined in equation 60.

The reference angle of attack was computed as:

$$\alpha_{ref} = \tan^{-1}\left(\frac{w_{b_{ref}}}{u_{b_{ref}}} \right) \quad \text{(deg)} \tag{A8}$$

and the reference sideslip from:

$$\beta_{ref} = \sin^{-1}\left(\frac{v_{b_{ref}}}{Vt_{ref}} \right) \quad \text{(deg)} \tag{A9}$$

The wing boom balsa vanes measure the flank angle rather than the sideslip angle. The reference flank angle was computed as:

$$\eta_{ref} = \tan^{-1}\left(\frac{\tan\beta_{ref}}{\cos\alpha_{ref}} \right) \quad \text{(deg)} \tag{A10}$$

Reference Static Pressure Calculation

The reference static pressure was determined by extrapolating the surface measurements to the probe altitude assuming a standard density lapse rate. Time histories of the ground static pressure and temperature measurements from the OV-10 are shown in figures A3 and A4, respectively. Also shown in figure A3 are the static pressure measurements from an independent ground measurement. The altitude of each probe was determined from the differential Ashtech GPS measurement and the INS attitude measurement.

$$h_j = 3.281 \cdot HI - (x_b - x_j)\sin\theta_{93} + (y_b - y_j)\cos\theta_{93}\sin\phi_{93} + (z_b - z_j)\cos\theta_{93}\cos\phi_{93} \quad \text{(ft)}$$
$$j = l, n, r \tag{A11}$$

The reference static pressure was computed from:

$$Ps_{ref,j} = Ps_{grnd} - g \cdot \rho_{mid,j}(h_j - h_{grnd})/144 \quad \text{(psi)}$$
$$j = l, n, r \tag{A12}$$

The density at the mid-altitude point was computed as:

$$\rho_{mid,j} = \rho_{grnd} + \frac{1}{2}(h_j - h_{grnd})\frac{d\rho}{dh} \quad (\text{slugs/ft}^3)$$
$$j = l, n, r \tag{A13}$$

with $\frac{d\rho}{dh} = -6.8\times10^{-7}$ slugs/ft^4 (standard density lapse rate). The air density at the ground was corrected for non-standard conditions through:

$$\rho_{grnd} = \frac{144 \cdot Ps_{grnd}}{R \cdot T_{grnd}} \quad (\text{slugs/ft}^3) \tag{A14}$$

with $R = 1716.5 \frac{\text{ft lb}}{\text{slug}\ ^\circ\text{R}}$.

Compute Position Error Correction

The position error correction was determined via a least squares linear-fit of the difference between the probe and reference static pressures as a function of the probe dynamic pressure.

Probe Static and Dynamic Pressure Calculation

The probe static and dynamic pressures were corrected for local flow angularity based on wind tunnel derived calibration coefficients. The static and dynamic pressure coefficients are defined as:

$$C_S = \frac{Ps_{ref} - Ps_{probe}}{q_{ref}} \tag{A15}$$

and

$$C_q = \frac{q_{ref} - q_{probe}}{q_{ref}} \tag{A16}$$

The reference values (subscripted *ref*) were the wind tunnel "truth" measurements. For the wing tip mounted NACA probes the coefficients were determined via a two-dimensional table lookup as a function of the reference angle of attack and sideslip. Tables 3 and 4 list the C_S and C_q table lookup values. The corrected wing tip probe dynamic (q_c) and static (Ps_c) pressures were computed from equations 29 and 30, respectively. The nose boom 5-hole probe dynamic (q_5) and static (Ps_5) pressures were computed from equations 20 and 21, respectively.

The position-error pressure correction was computed as the difference between the calibrated probe measurement and the reference value.

$$\begin{aligned} &\Delta Pq_j = Ps_{c,j} - Ps_{ref,j} \quad \text{(psi)} \\ &j = l, r \end{aligned} \tag{A17}$$

$$\Delta Pq_n = Ps_5 - Ps_{ref,n} \tag{A18}$$

Figures A5, A6, and A7 show the position error values of the nose, left and right boom probes, respectively, as a function of the probe calibrated dynamic pressure for the zero sideslip passes of both flights. Also shown on the figures is the least squares linear fit to the data. The linear fit coefficients were used as the position error correction coefficients for zero sideslip.

The effect of sideslip on the position error was determined by subtracting the zero sideslip position correction from the position error values at nonzero sideslip.

$$\Delta Pq_\beta = \Delta Pq_{(\beta \neq 0)} - \Delta Pq_{Fit(\beta=0)} \tag{A19}$$

Figures A8, A9, and A10 show the position error values due to sideslip of the nose, left and right boom probes, respectively. Also shown on the figures is the least squares linear fit to the data. The linear fit coefficients were used as the position error correction coefficients for non-zero sideslip. For the nose boom probe the effect of sideslip was symmetric about zero sideslip. For the wing tip probes the linear fit varied for positive and negative sideslip angles. The left and right boom corrections were nearly mirror images of each other. Figure A11 shows the two data sets combined with the left being the opposite sign as the right. The linear fit of the combined data sets was used for the tip boom correction coefficients.

The position error correction is applied to the static and dynamic pressure measurements through equations 36 through 39.

Angle of Attack Calibration

The angle of attack calibration was determined via a least squares linear fit of the measured value as a function of the reference value obtained from equation A8. The nose boom measured angle of attack was determined from equation 18. The wing tip values were obtained from the balsa vane measurements.

The airplane angular rates were assumed to be negligible. The data and linear fits are shown in figures A12, A13, and A14 for the nose, left and right booms, respectively. There was an apparent offset in the wing tip angle of attack measurements between flights 613 and 614. This was presumably due to a slight warping of the balsa vane with variation in temperature and humidity. Due to this offset the slope of the right and left boom calibration was computed from flight 613 values only. Flight 613 had a larger variation in the range of angles than Flight 614. The wing tip offset values for flight 614 were then computed using the slope calculations from flight 613.

Sideslip Angle Calibration

The sideslip calibration was determined in a similar manner as the angle of attack calibration. The reference sideslip value was obtained from equation A9. The nose boom measured sideslip angle was determined from equation 19. Figure A15 shows the nose boom sideslip calibration. There was a slight unresolved offset in the nose boom measurements between flights 613 and 614. The slope of the nose boom calibration curve was determined from flight 614 data since the majority of the sideslip data was obtained on that flight.

Figures A16 and A17 show the flank angle data and calibration for the left and right boom, respectively.



Figure A1(a). Surface wind history for Flight 613.



Figure A1(b). Surface wind history for Flight 614.



Figure A2(a). Wind laps rate history for Flight 613.



Figure A2(b). Wind laps rate history for Flight 614.



Figure A3(a). Ground static pressure history for Flight 613.



Figure A3(b). Ground static pressure history for Flight 614.



Figure A4. Ground temperature history for flights 613 and 614.



Figure A5. Nose boom 5-hole probe position error correction.



Figure A6. Left wing tip boom probe position error correction.



Figure A7. Right wing tip boom probe position error correction.



Figure A8. Nose boom probe position error correction with sideslip.



Figure A9. Left boom probe position error correction with sideslip.



Figure A10. Right boom probe position error correction with sideslip.



Figure A11. Combined right and left probe position error correction with sideslip.



Figure A12. Nose boom angle of attack calibration.



Figure A13. Left boom angle of attack calibration.



Figure A14. Right boom angle of attack calibration.



Figure A15. Nose boom sideslip calibration.



Figure A16. Left boom sideslip calibration.



Figure A17. Right boom sideslip calibration.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1. AGENCY USE ONLY (*Leave blank*)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
	September 1999	Technical Memorandum

4. TITLE AND SUBTITLE
Flight Data Reduction of Wake Velocity Measurements Using an Instrumented OV-10 Airplane

5. FUNDING NUMBERS
WU 538-04-11-12

6. AUTHOR(S)
Dan D. Vicroy, Robert A. Stuever, Eric C. Stewart, and Robert A. Rivers

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
NASA Langley Research Center
Hampton, VA 23681-2199

8. PERFORMING ORGANIZATION REPORT NUMBER
L-17892

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)
National Aeronautics and Space Administration
Washington, DC 20546-0001

10. SPONSORING/MONITORING AGENCY REPORT NUMBER
NASA/TM-1999-209552

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT
Unclassified-Unlimited
Subject Category 03 Distribution: Nonstandard
Availability: NASA CASI (301) 621-0390

12b. DISTRIBUTION CODE

13. ABSTRACT *(Maximum 200 words)*
A series of flight tests to measure the wake of a Lockheed C-130 airplane and the accompanying atmospheric state have been conducted. A specially instrumented North American Rockwell OV-10 airplane was used to measure the wake and atmospheric conditions. An integrated database has been compiled for wake characterization and validation of wake vortex computational models. This paper describes the wake-measurement flight-data reduction process.

14. SUBJECT TERMS
Wake Vortex, Flight Test, Wake Encounters, Data Reduction

15. NUMBER OF PAGES
66

16. PRICE CODE
A04

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
Unclassified	Unclassified	Unclassified	UL